AGGREGATE INDUSTRIES

MATERIAL SAFETY DATA SHEET

FILE NO.: Jet Sand
MSDS DATE: January 1, 2008

SECTION 1: PRODUCT AND COMPANY IDENTIFICATION

PRODUCT: **JET SAND**

DESCRIPTION: **Granular Mineral**

MANUFACTURER: **Aggregate Industries, Inc.**
ADDRESS: **7529 Standish Pl.**
Rockville, MD 20855

EMERGENCY PHONE: **(301) 284-3617**
POISON CONTROL: **(800) 222-1222**

PRODUCT USE: **Surfacing agent for airport runways and taxiways.**
Do not use this product for abrasive sanding.

SECTION 2: COMPOSITION/INFORMATION ON INGREDIENTS

CAS NO.		% WT	OSHA PEL-TWA: mg/m3	ACGIH TLV-TWA: mg/m3
14808-60-7	Crystalline Silica	> 90	(10) / (%SiO_2 + 2)] Respirable [(30) / (%SiO_2 + 2)] Total	0.05 Respirable
Water				

SECTION 3: HAZARDS IDENTIFICATION

EMERGENCY OVERVIEW: Respirable crystalline silica (quartz) is a hazard of sand products. Crystalline silica is classified as a known human carcinogen be the International Agency for Research on Cancer (IARC), the National Toxicology Program (NTP) and California Proposition 65. Prolonged and repeated exposures to airborne dust containing respirable crystalline silica can cause chronic diseases such as silicosis, a lung disease which can be disabling and fatal, and lung cancer. When exposed to airborne dusts, use appropriate ventilation controls, and/or dust suppression measures (e.g., water streams or mists) and personal protective equipment (PPE) as described in Section 8.

Engulfment hazard. To prevent burial or suffocation, do not enter a confined space, such as a silo, bin, bulk truck, or other storage container or vessel which stores or contains sand products. Sand can build up or stick to the walls of a confined space. The sand can release, collapse or fall unexpectedly.

Do not stand on stockpiles of sand because they may be unstable. Use engineering controls (e.g., wet down stockpiles with water) to prevent windblown dust from stockpiles.

Bagged sand products are heavy and pose hazards such as sprains and strains to the back, legs, arms and shoulders during lifting and mixing. Make sure stacked bagged material is securely stored to prevent falling. Use appropriate control measures when handling.

ROUTES OF ENTRY: Inhalation, Skin, Eye Contact, and Ingestion

POTENTIAL HEALTH EFFECTS

EYES: **Airborne dust contacting the eyes may cause immediate or delayed irritation or inflammation. Exposure to large amounts of sand can cause moderate eye irritation from abrasion. Eye exposures require immediate first aid and medical attention to prevent serious damage to eyes.**

AGGREGATE INDUSTRIES

MATERIAL SAFETY DATA SHEET

FILE NO.: Jet Sand
MSDS DATE: January 1, 2008

SKIN: **Sand may cause dry, irritated skin and abrasions.**

INGESTION: **Ingesting small amounts of sand is not known to be harmful, but ingestion of large amounts can cause digestive tract distress. Contact the Poison Control Center at (800) 222-1222.**

INHALATION:

Acute: **Depending on the airborne concentration and the duration of exposure, breathing dust from sand products may cause nose, throat, or respiratory tract irritation.**

Chronic: **Prolonged and repeated exposures to airborne dust containing respirable crystalline silica can cause chronic diseases such as silicosis, a lung disease which can be disabling and fatal, and lung cancer. Respirable crystalline silica (quartz) is listed as a known human carcinogen by the International Agency for Research on Cancer (IARC), the National Toxicology Program (NTP) and California Proposition 65.**

MEDICAL CONDITIONS GENERALLY AGGRAVATED BY EXPOSURE:

Persons with lung disease such as bronchitis, emphysema, COPD (Chronic Obstructive Pulmonary Disease), and other pulmonary diseases can be aggravated by exposure to airborne dusts.

SECTION 4: FIRST AID MEASURES

EYES: **Do not rub eyes. Immediately flush eyes with lots of clean water for at least 15 minutes. Flush under eyelids to remove all particles. Seek medical attention. An eye exam is recommended. It may take 2 to 3 days after the exposure to assess condition of eyes.**

SKIN: **Wash with clean water and a pH neutral soap or a mild soap detergent for at least 15 minutes. Seek medical attention for irritation and rashes.**

INGESTION: **Sand is not meant to be eaten. Seek medical attention if gastric irritation occurs.**

INHALATION: **Move person to fresh air. Seek medical attention for discomfort or if coughing and other symptoms do not stop.**

SECTION 5: FIRE-FIGHTING MEASURES

FLAMMABLE LIMITS IN AIR (% BY VOLUME): **Not flammable or combustible**

FLASH POINT: **Not Applicable**
METHOD USED: **Not Applicable**

AUTOIGNITION TEMPERATURE: **Not Applicable**

NFPA HAZARD CLASSIFICATION

HEALTH:	**3**	**FLAMMABILITY: 0**	**REACTIVITY: 0**	**0 = Minimal Hazard**
				1 = Slight Hazard
HMIS HAZARD CLASSIFICATION				**2 = Moderate Hazard**
HEALTH:	***3**	**FLAMMABILITY: 0**	**REACTIVITY: 0**	**3 = Serious Hazard**
				4 = Severe Hazard

- **Respirable crystalline silica can cause lung disease and/or lung cancer**

PROTECTION: E – Safety glasses, gloves and dust respirator

EXTINGUISHING MEDIA: Use extinguishing media appropriate for surrounding fire.

AGGREGATE INDUSTRIES

MATERIAL SAFETY DATA SHEET

FILE NO.: Jet Sand
MSDS DATE: January 1, 2008

SPECIAL FIRE FIGHTING PROCEDURES: **Sand products do not pose a fire-related hazard. A SCBA is recommended to limit exposures to combustion products when extinguishing any fire.**

UNUSUAL FIRE AND EXPLOSION HAZARDS: **None**

HAZARDOUS DECOMPOSITION PRODUCTS: **None**

SECTION 6: ACCIDENTAL RELEASE MEASURES

ACCIDENTAL RELEASE MEASURES: **Place spilled material in suitable containers for disposal. Avoid procedures which generate dust. If dust is generated, wear appropriate protective equipment as described in Section 8.**

WASTE DISPOSAL METHOD: **Dispose of sand according to Local, State, Provincial and Federal regulations.**

SECTION 7: HANDLING AND STORAGE

HANDLING AND STORAGE:

Stack bagged material in a secure manner to prevent falling. Bagged sand is heavy and poses hazards such as sprains and strains to the back, legs, arms and shoulders during lifting and mixing.

Engulfment hazard. To prevent burial or suffocation, do not enter a confined space, such as a silo, bin, bulk truck, or other storage container or vessel which stores or contains aggregates. Sand can build up or stick to the walls of a confined space. The sand can release, collapse or fall unexpectedly.

Do not stand on stockpiles of sand because they may be unstable. Use engineering controls (e.g., wet down stockpiles with water) to prevent windblown dust from stockpiles.

OTHER PRECAUTIONS: **Avoid actions which cause sand to become airborne during clean – up such as dry sweeping or using compressed air. Use HEPA vacuum or thoroughly wet with water to clean – up dust. Use PPE described in Section 8.**

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

ENGINEERING CONTROLS: **Use local exhaust or general dilution ventilation or other suppression methods to maintain dust levels below exposure limits.**

RESPIRATORY PROTECTION: **Under normal conditions no respiratory protection is required. In dusty conditions and where engineering controls are not feasible, NIOSH/MSHA approved respirators must be worn in accordance with a respiratory protection program which meets OSHA requirements as set forth at 29 CFR 1910.134 and ANSI Z88.2 – 1080 "Practices for Respiratory Protection."**

EYE PROTECTION: **Wear ANSI – approved glasses or safety goggles when handling this product and where dust is generated. Do not wear contact lenses when involved with activities which generate dust.**

SKIN PROTECTION: **Wear gloves when handling sand products. Remove clothing and protective equipment that becomes dusty and launder and clean before re-using.**

AGGREGATE INDUSTRIES

MATERIAL SAFETY DATA SHEET

FILE NO.: Jet Sand
MSDS DATE: January 1, 2008

WORK HYGIENIC PRACTICES: **Avoid creating and breathing dust.**

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

APPEARANCE:	**Light brown granular solid**
ODOR:	**None**
PHYSICAL STATE:	**Solid**
pH:	**7**
BOILING POINT:	**None, Solid**
MELTING POINT:	**None, Solid**
FREEZING POINT:	**None, Solid**
VAPOR PRESSURE (mmHg):	**Not applicable**
VAPOR DENSITY (AIR = 1):	**Not applicable**
SPECIFIC GRAVITY (H2O = 1):	**2.5 – 2.8**
EVAPORATION RATE:	**Not applicable**
SOLUBILITY IN WATER:	**Negligible**
PERCENT SOLIDS BY WEIGHT:	**100 %**
PERCENT VOLATILE:	**0 %**

SECTION 10: STABILITY AND REACTIVITY

STABILITY:	**Stable**
CONDITIONS TO AVOID (STABILITY):	**None**
INCOMPATIBILITY (MATERIAL TO AVOID):	**Reactive to strong oxidizing agents. Hydrofluoric acid dissolves silica to produce corrosive silicon tetrafluoride gas. Acids react to produce heat. Nitro-organic compounds may react to form explosive salts.**
HAZARDOUS DECOMPOSITION OR BY-PRODUCTS:	**None**
HAZARDOUS POLYMERIZATION:	**Will not occur**

SECTION 11: TOXICOLOGICAL INFORMATION

TOXICOLOGICAL INFORMATION: **Repeated, prolonged exposure to respirable crystalline silica can cause silicosis and lung cancer. Silicosis is a disabling, nonreversible and sometimes fatal lung disease. The development of silicosis may increase the risk of additional diseases.**

SECTION 12: ECOLOGICAL INFORMATION

ECOLOGICAL INFORMATION: **None known.**

AGGREGATE INDUSTRIES

MATERIAL SAFETY DATA SHEET

FILE NO.: Jet Sand
MSDS DATE: January 1, 2008

SECTION 13: DISPOSAL CONSIDERATIONS

WASTE DISPOSAL METHOD: **This product is classified as a non-hazardous solid waste for disposal. Dispose of waste in compliance with applicable Local, State, Provincial and Federal regulations.**

SECTION 14: TRANSPORT INFORMATION

U.S. DEPARTMENT OF TRANSPORTATION

PROPER SHIPPING NAME: **Same as product name**
HAZARD CLASS: **Not classified as hazardous**
ID NUMBER: **None**
PACKING GROUP: **None**
LABEL STATEMENT: **Not applicable**

SECTION 14 NOTES: **This product is not classified as hazardous under U.S. DOT or Canadian TDG regulations.**

SECTION 15: REGULATORY INFORMATION

U.S. FEDERAL REGULATIONS

TSCA (TOXIC SUBSTANCE CONTROL ACT): **Not listed.**

CERCLA (COMPREHENSIVE RESPONSE COMPENSATION, AND LIABILITY ACT): **Not listed.**

SARA TITLE III (SUPERFUND AMENDMENTS AND REAUTHORIZATION ACT): **Not listed under Sections 302, 304 and 313.**

OSHA: **Dust and respirable crystalline silica generated during product use may be hazardous.**

RCRA: **If discarded in its purchased form, this product would not be a hazardous waste either by listing or characteristic. Under RCRA it is the responsibility of the product end user to determine at the time of disposal, whether a material containing the product or derived from the product should be classified as a hazardous waste.**

STATE REGULATIONS: **California Proposition 65 – Respirable crystalline silica.**

CANADIAN REGULATIONS: **This product has been classified in accordance with the hazard criteria of the Controlled Products Regulations and the MSDS contains all the information required by the Controlled Products Regulations. All components of this product are included in the Canadian Domestic Substances List (DSL).**

AGGREGATE INDUSTRIES

MATERIAL SAFETY DATA SHEET

FILE NO.: Jet Sand
MSDS DATE: January 1, 2008

SECTION 16: OTHER INFORMATION

Abbreviations:

< **>** **≥**	**Greater than** **Less than** **Equal to or greater than**	**NA**	**Not Applicable**
ACGIH	**American Conference of Governmental Industrial Hygienists**	**NFPA**	**National Fire Protection Association**
CAS No	**Chemical Abstract Number**	**NIOSH**	**National Institute for Occupational Safety and Health**
CERCLA	**Comprehensive Environmental Response, Compensation and Liability Act**	**NTP**	**National Toxicology Program**
CFR	**Code of Federal Regulation**	**OSHA**	**Occupational Safety and Health Administration**
CL	**Ceiling Limit**	**PEL**	**Permissible Exposure Limit**
DOT	**US Department of Transportation**	**pH**	**Negative log of hydrogen ion**
EST	**Eastern Standard Time**	**PPE**	**Personal Protective Equipment**
HEPA	**High-Efficiency Particulate Air**	**R**	**Respirable particulate**
HMIS	**Hazardous Materials Identification System**	**RCRA**	**Resource Conservation and Recovery Act**
IARC	**International Agency for Research on Cancer**	**SARA**	**Superfund Amendments and Reauthorization Act**
LC_{50}	**Lethal Concentration**	**T**	**Total particulate**
LD_{50}	**Lethal Dose**	**TDG**	**Transportation of Dangerous Goods**
mg/m^3	**Milligrams per cubic meter**	**TLV**	**Threshold Limit Value**
mppcf	**Million particles per cubic foot**	**TWA**	**Time Weighted Average (hours)**
MSHA	**Mine Safety and Health Administration**	**WHMIS**	**Workplace Hazardous Materials Information System**

THE INFORMATION RELATES TO THIS SPECIFIC MATERIAL. IT MAY NOT BE VALID FOR THIS MATERIAL IF USED IN COMBINATION WITH OTHER MATERIALS OR IN ANY PROCESS. IT IS THE USER'S RESPONSIBILITY TO SATISFY ONESELF AS TO THE SUITABILITY AND COMPLETENESS OF THIS INFORMATION FOR HIS OWN PARTICULAR USE. ALL MATERIALS MAY PRESENT UNKNOWN HAZARDS AND SHOULD BE USED WITH CAUTION. ALTHOUGH CERTAIN HAZARDS ARE DESCRIBED HEREIN, WE CANNOT GUARANTEE THAT THESE ARE THE ONLY HAZARDS THAT EXIST.